



version 1.0

2018 BROCHURE



Cultivation Incubators



Winpact Shaker

WS-200 / WS-201



- Various speed settings from 20-500 rpm
- Equipped with a robust brushless DC motor for economical and noiseless operation
- Two modes of operation available: programmable or continuous
- Versatile accessories available for advanced culturing solutions
- Auto detection and power shutdown to platform weight imbalance or belt breakage



Cat. No.	WS-200	WS-201
Description	Winpact Orbital Shaker (universal platform included)	Winpact Orbital Anti-moistured Shaker (universal platform included)
Platform size	460 x 460 mm	
Shaking orbit	19 mm	
Speed range	20-500 rpm	
Speed increment	1 rpm	
Timer	999 (hr): 59 (min) / Continuous	
Display	3.5" Color TFT LCD screen	
Dimension (WxLxH)	Approx. 520 x 620 x 210 mm	
Rated Voltage	100-240V~, 50 / 60Hz, 2A	
Loading Capacity *	Approx. 500 rpm: 5 kg, 250 rpm: 30 kg	
Weight	Approx. 40kg	

* Different flask will reduce the maximum speed.



Winpact Shaking Incubator

SI-200



- Special designed drainage channel protects the motor and inner circuitry from accidental spills
- Multiple early error-detection mechanisms ensure operators' safety and completeness of experiment despite malfunction
- Lab-proven superior temperature uniformity
- A wide selection of racks, holders, sticky pads and accessories provides all-ranged compatibility to cell cultivation labwares
- Automatic system shutdown in the event of system over-heating
- Sensitivity adjustable G-sensor with warning embedded for imbalance weight detection
- Programmable or continuous mode for personnel operation
- Brushless DC motor provides long and quiet operation, durable and maintenance-free usage
- Hermetic chamber design significantly reduces operation noise and enhances precise temperature control
- 2-point temperature calibration ensures high temperature performance



A spare air/gas inlet to create particular environment for specific kinds of cell/microbial

Cat. No.	SI-200 (universal platform included)
Platform size	460 x 460 mm
Shaking orbit	19 mm
Speed range	20-500 rpm
Speed increment	1 rpm
Communication port	RS-485
External temperature probe	PT-100
Heating temperature range	Ambient +5°C to 65°C
Power	600W
Temp accuracy and uniformity	± 0.25°C at 37°C
Timer	999 (hr) : 59 (min) / Continuous
Display	3.5" Color TFT LCD screen
Dimension (W x L x H)	Approx. 590 x 820 x 530 mm



Acrylic lid for clear viewing and easy access



Universal platform Cat. No.: SI-200-01	Adjustable angle tube rack (33 x 15 ml) Cat. No.: SI-200-02	Adjustable angle tube rack (16 x 50 ml) Cat. No.: SI-200-03	Universal spring rack Cat. No.: SI-200-04	Sticky pad platform Cat. No.: SI-200-05	Universal cushioned crossbar Cat. No.: SI-200-06	Microplate holders Cat. No.: SI-200-07 (platform not included)	Flask holder Cat. No.: SI-200-08~13

*tube not included

*All technical specifications are subject to change without notice.

*Please visit our website at www.majorsci.com for more product selection and detailed information.

US Office

19959 Sea Gull Way
Saratoga, CA 95070
U.S.A.
T/ +1-408-366-9866
F/ +1-408-446-1107

Taiwan Office

No.19, Ln. 207, Huakang St.
Bade Dist., Taoyuan City 33464
Taiwan
T/ +886-3-3623319
F/ +886-3-3623133

Shanghai Office

Room 612, International business exhibition center,
9300 Hunan Road, Pudong, Shanghai, China
National toll-free No.:400-823-9177
T/ +86-21-50795277
F/ +86-21-50795277

India Office

D. No. 12-13-99, Satguru Apts. Extn.
Street. No. 3, Lane No.1, Tarnaka
Secunderabad – 500 017. India
T/ +91-40-27001515
T/ +91-40-27001586



www.majorsci.com

info@majorsci.com